

LC6 Laboratory Temperature Controller

Temperature Controller

JULABO Temperature Controllers fulfill temperature-dependent measurement, control, safety and monitoring tasks. Modern control technology, space-saving design and high operating comfort are particular advantages. The units offer MULTI-DISPLAY (LED) and a splash-proof keypad. High and low temperature warning functions with an interval tone (patented) ensure safe operation. The built-in RS232 interface enables online communication with a PC. Typical applications: heating mantles, heating baths and heating mats.



Your advantages

- PID temperature control
- Bright, large LED display
- Constant indication of setpoint and actual values
- Splash-proof keypad
- Adjustable high temperature cut-off
- RS232 interface
- Analog programmer input and temperature recorder output
- Connections for 3 Pt100 sensors (working & safety)

Technical Data

Order No.	9700160
Model series	LC Series
Category	Laboratory Temperature Controllers
Working temperature range (°C)	-100 ... +400
Temperature stability (°C)	±0.01
Setting / display resolution	0.01
Temperature Display	LCD, LED
Heating capacity (kW)	3
External Pt100 sensor connection	integrated
Digital interface	RS232, RS485 Optional: Profibus
Analog connection input / output	Yes
Ambient temperature	5...40 °C
Dimensions W x L x H (cm)	21 x 18 x 18
Weight (kg)	4
Power requirement V / Hz / A	230/50-60/14
Temperature stability in external system °C	>± 0.03
LED display / resolution °C	1 / 0.01 °C
LCD display / resolution °C	1 / 0.01 °C
Safety sensor control	1 x Pt100
Working sensor	2 x Pt100

Maximum connection wattage	3
Available voltage versions	230 V / 50 - 60 Hz

Characteristics

Display



Several values at a glance

Large Multi-Display (LED), easy to read across the room, for actual value and up to 3 setpoints, warning functions, high temperature cut-off, selected pump stages (resolution 0.01/0.1 °C)

Warning & Safety Functions



Early warning system for high/low temperature limits

Maximum safety for applications, optical and audible alarm, convertible to automated cut-off function

Operation



Clearly structured

Comfortable, splash-proof keypad for setpoint adjustment, high/low temperatures, timer and shaking frequency (SW models)

Temperature Control



Precise

PID Temperature control with set control parameters, temperature stability $\pm 0.02 \dots \pm 0.2$ °C



High measuring accuracy

'Absolute Temperature C alibration' for manual compensation of a temperature difference, 1-point calibration

Technical Features



Control from the external application

External Pt100 sensor connection for precise measurement and control directly in the external application



Serial connection

RS232 interface for PC connection, e.g. for data communication and recording of measured values